

FILE PREPARATION

RASTER IMAGE RESOLUTION REQUIREMENTS:

Resolution at Full Size	Maximum	Preferred	Minimum
FINE ART	200	150	100
DISPLAY QUALITY	150	100	75
BILLBOARD	50	25	12.5
OFFSET PRINTING	400	300	300

Resolution at 1/12th Scale	Maximum	Preferred	Minimum
FINE ART	2400	1800	1200
DISPLAY QUALITY	1800	1200	900
BILLBOARD	600	300	150

- **FINE ART-** Canvas, Photo, Watercolor
- **DISPLAY QUALITY-** Banners, Stage Backdrops, Mesh Banner, UV Printing, Adhesive Vinyl, Wallpaper, Duratrans
- **BILLBOARD-** Billboard, Building Wrap Mesh
- **RIGID SHEETS-** Sintra, Gator Board, Lexan
- **FABRIC-** SEG, Backlit and Front lit
- **OFFSET PRINTING-** Business Cards, Post Cards, Brochures, Flyers

SIZING:

- Files under 200" can be built at full size. Files larger than 200" must be built at scale, (1:2, 1:4, 1:10, 1:12, etc.).

FILE FORMATS:

- **Photoshop-** PSD, TIFF, EPS, PDF, JPEG, PNG
- **InDesign-** PDF/native files preflighted & packaged for output
- **Illustrator-** AI, EPS, PDF (outline all fonts, and embed any linked graphics)
- Any other graphic program capable of creating an acceptable PDF, TIFF, EPS, JPEG, PNG file

TROUBLE SHOOTING:

- Never set anything to overprint
- Graphics with multiple blending mode layers: flatten effects to avoid issues with the rip conversion.
- When using solid areas of black, build a new color in the color list "Rich Black" with the following color values; Cyan 60%, Magenta 60%, Yellow 40%, Black 100%. This will give your print a richer/denser feel. (Note: this is only for large black ink areas. DO NOT use rich black for small text or thin lines or run the risk of blurring your image)
- In the process color mode using Cyan, Magenta, Yellow, and Black ink, not all PMS colors can be matched 100%. Blues in the CMYK process will begin to shift towards purple with less than a 30% difference between the Cyan and Magenta

COLORSPACE:

- All files should be in CMYK color space except for Canvas, Photo, Watercolor, and Duratrans which should be supplied in RGB. Embedded color profiles should set to US Web Coated (SWOP) V2 for CMYK files and Adobe RGB (1998) for RGB FILES.

BLEED:

All files should include .125" bleed on all sides except:

- **Billboards** with pockets which require 6" of bleed on all sides (.5" at 1/12th scale)
- **Gallery Wrap Canvas prints** require .625" bleed for standard bars or 1.625" for heavy duty bars
- **Fabric prints** require 1.5" bleed on all sides for SEG and non SEG fabric panels.

UPLOAD:

- File transfer options include: WeTransfer, Hightail, Box, or Dropbox links. Compress or Zip any multi-file jobs into one folder. If using the FTP to transfer images, please notify us when the files have completed their upload.



QUESTIONS?

888-674-4033

SALES@DTPH.COM